



ENTRON™

Controls for Resistance Welding

EN6041



Single Phase AC Cascade Constant Current Controls

Cascade Firing of up to 8 Contactors

- Part of the EN6000 Series family with common hardware and programming
- 300 Amp air-cooled and 1200, 1800, 2200 & 3200 Amp water-cooled Contactors available
- Shorted contactor detection on all contactors
- Extremely flexible Heat Control allows 2 welds for every schedule programmed to Constant Current or Phase Shift Current on any contactor individually selectable
- 8 independent Valve Outputs control relay protected and monitored
- Standard I/O features provide additional 16 inputs and 8 outputs as compared to EN6021 Controls
- Similar in programming and operation to EN1000 Series Controls
- Only one Primary or Secondary Coil required

Constant Current

- Control adjusts current output every cycle.
- No setup necessary for constant current operation.
- When optional secondary or primary coil is used, secondary amps are directly displayed.
- Current High, Low and Pre limits.
- Results of last weld available immediately.
- Pulse Width Monitor

PLC Compatible

- PLC compatible via EtherNet/IP or MODBUS Function Code 04, 16 and 43 through low-cost serial (RS232 and RS485) or ethernet interfaces
- Design custom operator interface
- Actuate Weld Control Inputs from PLC, minimal interconnecting wires required
- Use weld control I/O for remote PLC I/O



ENLINK 6041

*Standard with
every control !*

Communication software provides PC interface for USB or Ethernet interfaces.

Features

- USB B interface for ENLINK programming
- USB A Memory Stick Jack for Schedule backup
- USB A Memory Stick Jack for Weld Log and Error Log storage
- Spot or Pulsation Sequence
- Programmable options: Slope, Preheat, Quench, Temper, Postheat
- Linked Programs
- External Schedule Select
- Event Outputs
- Advanced Error Outputs
- 100 Programs
- Non-Repeat
- Water Saver Timer
- Programming in phase shift or kA
- 24 VDC flexible I/O (40 in/24 out); some mapable between weld functions, events and simple I/O sequences (32 in/24 out available for sequencer) with output protection
- I/O Sequencer/Programmer
- Stepper with Force and Current Presets
- Diverse schedule capabilities provide maximum application versatility
- 2) each 4-20 mA / 0-10V analog input & output provided for pressure sensing & control
- Program Select
- Weld Log (57,600 entries) and Error Log (1,000 entries) with real time clock
- Shorted contactor detection

Options

- Detachable 128 x 64 dots graphic (8 lines) LCD Program Pendant (RPP2) with data backup and 10' cable
- Primary or Secondary coils
- Program Lockout
- Operation Mode Switch (OMS) – Program Lockout & Weld/No Weld
- Error Reset Switch (ERS)
- Pressure Sense & Proportional Valve
- Isolation Contactor
- GFI for portable guns
- Water Flow Switch
- RS232/485/Ethernet communication card
- USB Memory stick for backup
- Communication Services Controller


Exclusive ENTRON two year warranty



4 Cascade Control in 'G' Cabinet



Available Contactor Sizes: 300, 1200, 1800, 2200, 3200 Amp



Options (Expanded Capabilities require additional software and/or hardware)

TO PROGRAM, YOU WILL NEED:

Program Pendant (RPP2)

(P/N 730014-001)
Detachable, hand-held pendant accesses all programmable variables and displays current and status.



- OR - ENLINK 6041

(P/N 730015-001)
Communication software provides PC interface for remote programming and monitoring of control.



• Pressure Sense and Control Hardware

Using provided analog I/O or additional hardware:
Differential sensors (P/N 730005-008)
Single-ended sensors (P/N 730005-005)
Proportional valves:
1/2" port (P/N 730005-007)
1 1/4" port (P/N 730005-006)



• Communication Cards

(P/N 730014-007 & 730014-013)
Provides ability to network multiple controls using ENLINK 6041.



• External USB & Ethernet Connectors

(P/N 730014-002)



TO MEASURE CURRENT IN AMPS, YOU WILL NEED:

Secondary Rogowski Coils

(S5 - P/N 730014-005; S8 - P/N 730014-006)
Available in 5" or 8" diameters.
Provides actual secondary amperage measurements.



- OR -

Coil as part of Weld Transformer.

- OR -

Primary Coil (P/N 313022)



• Operation Mode Switch (OMS)

(P/N 730014-004)



• Program Lockout (PLS)

(P/N 730014-009)



• Error Reset Switch (ERS)

(P/N 730014-015)



• Data storage on USB memory stick

(P/N 730014-003)




• Communication Services Controller (CSC)

(P/N 730014-016)
Provides bridge to ControlLogix, Web Browser ENLINK, and FTP Services



• RS232 Printer

(P/N 730014-011)



• Water Flow Switch

(P/N 730005-009)



Distributed by:

ENTRON™

ENTRON Controls, LLC.
1402 S. Batesville Road
Greer, SC 29650
(864) 416-0190
FAX (864) 416-0195
www.entroncontrols.com
e-mail: info@entroncontrols.com

